



DIMENSION	4"	4"	4"	6"	6"	6" x 4"	8"
	Class 150	Class 300	Class 600	Class 150	Class 300	Class 600	Class 150
A (SR)	18"	20"	25"	N/A	N/A	27"	N/A
A (DA)	16-7/8"	19"	19-3/8"	22"	27-1/8"	21-3/4"	27-1/4"
B (SR)	16-5/8"	19-1/4"	25-3/8"	N/A	N/A	25-3/8"	N/A
B (DA)	10-1/4"	12"	12"	14-3/8"	19-3/8"	12"	19-3/8"
C (SR)	9-1/2"	10-3/8"	14" (NOTE 3)	N/A	N/A	14-1/2" (NOTE 3)	N/A
C (DA)	8-3/4"	10"	10"	11-7/8"	15-3/8" (NOTE 3)	10-5/8"	15"
D	4-1/2"	5"	5-3/8"	5-1/2"	6-1/4"	7"	6-3/4"
E	9"	10"	10-3/4"	11"	12-1/2"	14"	13-1/2"
F (SR)	3-1/16"	3-5/16"	4"	N/A	N/A	4"	N/A
F (DA)	2-9/16"	3-1/16"	3-1/16"	3-5/16"	4"	3-1/16"	4"
G (SR)	4-3/16"	4-1/4"	5"	N/A	N/A	5"	N/A
G (DA)	3"	4-3/16"	4-3/16"	4-1/4"	5"	4-3/16"	5"
H (SR)	5-9/16"	5-9/16"	6-3/8"	N/A	N/A	6-3/8"	N/A
H (DA)	4-3/8"	5-9/16"	5-9/16"	5-9/16"	6-3/8"	5-9/16"	6-3/8"
J (SR)	6-1/8"	6-5/8"	8"	N/A	N/A	8"	N/A
J (DA)	5-1/8"	6-1/8"	6-1/8"	6-5/8"	8"	6-1/8"	8"
K	9"	12"	17" (RF)	15-1/2"	15-7/8"	22" (RF)	18"
NOTE 1: "H" IS CENTERLINE TO OUTSIDE SURFACE OF SOLENOID- ADD 1-1/8" IF EQUIPPED WITH QUADRANT BREATHER BLOCK							
NOTE 2: ADD 3-3/8" TO "A" & "C" DIMENSIONS IF A DGO IS MOUNTED BETWEEN VALVE & C-SERIES ACTUATOR.							
NOTE 3: NEEDS 2-1/2" HIGH MOUNTING BRACKET BETWEEN ACTUATOR & VALVE							



Series F2-CS/SS with C-Series Pneumatic Actuator