



DIMENSION	2"	2-1/2"	3"	4"	5"	6"	8"	10"	12"	14"
A (SR)	14.8	16.6	17.2	19.2	21.4	22.3	27.9	others	others	others
A (DA)	14.2	15.0	16.3	18.4	19.5	21.2	25.4	28.7	37.8*	40.0*
B (SR)	8.1	9.9	9.9	14.0	16.7	16.7	25.3	others		
B (DA)	5.7	5.7	5.9	7.2	7.2	10.3	12.0	14.4	19.3	19.3
C (SR)	8.9	10.0	10.2	11.2	12.4	12.9	15.8			
C (DA)	8.6	9.2	9.7	10.8	11.3	12.2	14.5	16.1	22.8*	24.0*
D	3.3	3.6	3.9	4.6	5.1	5.6	7.0	8.1	9.6	10.6
F (SR)	1.7	2.1	2.1	2.5	2.7	2.7	3.8			
F (DA)	1.3	1.3	1.7	2.1	2.1	2.5	2.7	2.9	3.8	3.8
G (SR)	2.1	2.6	2.6	3.0	4.2	4.2	5.0			
G (DA)	1.9	1.9	2.1	2.6	2.6	3.0	4.2	4.3	5.0	5.0
H (SR)	3.5	4.0	4.0	4.4	5.6	5.6	6.4			
H (DA)	3.3	3.3	3.5	4.0	4.0	4.4	5.6	5.7	6.4	6.4
J (SR)	3.4	4.2	4.2	5.0	5.4	5.4	7.6			
J (DA)	2.6	2.6	3.5	4.2	4.2	5.0	5.5	5.7	7.6	7.6
K	1.7	1.8	1.8	2.1	2.2	2.2	2.4	2.7	3.1	3.1
NOTE: "H" IS CENTERLINE TO OUTSIDE SURFACE OF SOLENOID- ADD 1-1/8" IF EQUIPPED WITH QUADRANT BREATHER BLOCK										

Note: 1. Asterisk indicates use of 4" square mounting bracket
2. All dimensions in inches



**2" thru 14" Series BFV-D with C-Series Pneumatic Actuator
200PSID DRY SERVICE**