



DIMENSION	2"	2-1/2"	3"	4"	5"	6"	8"	10"	12"	14"
A (SR)	14.8	15.7	17.2	18.4	20.2	22.3	30.4*	34.5*	others	others
A (DA)	14.2	15.0	15.5	18.4	19.5	20.5	24.3	27.6	32.0	34.2
B (SR)	8.1	8.1	9.9	9.9	14.0	16.7	19.2	25.3	others	others
B (DA)	5.7	5.7	5.7	7.2	7.2	7.2	10.3	12.0	14.4	14.4
C (SR)	8.9	9.5	10.2	10.8	11.7	12.9	18.9*	21.0*		
C (DA)	8.6	9.2	9.4	10.8	11.3	11.8	13.8	15.6	17.9	19.1
D	3.3	3.6	3.9	4.6	5.1	5.6	7.0	8.1	9.6	10.6
F (SR)	1.7	1.7	2.1	2.1	2.5	2.7	2.9	3.8		
F (DA)	1.3	1.3	1.3	2.1	2.1	2.1	2.5	2.7	2.9	2.9
G (SR)	2.1	2.1	2.6	2.6	3.0	4.2	4.3	5.0		
G (DA)	1.9	1.9	1.9	2.6	2.6	2.6	3.0	4.2	4.3	4.3
H (SR)	3.5	3.5	4.0	4.0	4.4	5.6	5.7	6.4		
H (DA)	3.3	3.3	3.3	4.0	4.0	4.0	4.4	5.6	5.7	5.7
J (SR)	3.4	3.4	4.2	4.2	5.0	5.4	5.8	7.6		
J (DA)	2.6	2.6	2.6	4.2	4.2	4.2	5.0	5.4	5.8	5.8
K	1.7	1.8	1.8	2.1	2.2	2.2	2.4	2.7	3.1	3.1
NOTE: "H" IS CENTERLINE TO OUTSIDE SURFACE OF SOLENOID- ADD 1-1/8" IF EQUIPPED WITH QUADRANT BREATHER BLOCK										

Note: 1. Asterisk indicates use of 4" square mounting bracket
2. All dimensions in inches.



**2" thru 14" Series BFV-D with C-Series Pneumatic Actuator
200PSID WET SERVICE**