



F1-CS/SS CLASS 150/300 SIZE	MAX BREAK	VALVE ISO PATTERN	SQUARE STEM DRIVE	C-SERIES UNIT (SEE NOTE 1)	BRACKET NUMBER	BOLTING HARDWARE	DRIVE INSERT REQUIRED	DRIVER NUMBER
1/2"	100 IN-LB	F03	N/A	C-250(DA & SR)	B-4	(4) M6 x 1.0P x 12MM w/Lockwashers PLUS (3) 1/4"-20UNCx1/2" w/Lockwashers	NONE	D-10A
3/4"	140 IN-LB	F04	N/A	C-250(DA)	B-5	(4) M6 x 1.0P x 12MM w/Lockwashers	NONE	D-11A
3/4"	140 IN-LB	F04	N/A	C-450SR	B-5	PLUS (3) 1/4"-20UNCx1/2" w/Lockwashers	14M11	D-11A
1"	160 IN-LB	F04	N/A	C-250 (DA)	B-5	(4) M6 x 1.0P x 12MM w/Lockwashers	NONE	D-11A
1"	160 IN-LB	F04	N/A	C-450SR	B-5	PLUS (3) 1/4"-20UNCx1/2" w/Lockwashers	14M11	D-11A
1-1/2"	250 IN-LB	F07	14MM	C-450(DA)	NONE	(4) M8 x 1.25P x 20MM w/Lockwashers	NONE	NONE
1-1/2"	250 IN-LB	F07	14MM	C-1000SR	NONE	(4) M8 x 1.25P x 20MM w/Lockwashers	17M14	(DIRECT-MOUNT)
2"	400 IN-LB	F07	14MM	C-450(DA)	NONE	(4) M8 x 1.25P x 20MM w/Lockwashers	NONE	NONE
2"	400 IN-LB	F07	14MM	C-1000SR	NONE	(4) M8 x 1.25P x 20MM w/Lockwashers	17M14	(DIRECT-MOUNT)
2-1/2"	475 IN-LB	F07	14MM	C-1000(DA&SR)	NONE	(4) M8 x 1.25P x 20MM w/Lockwashers	17M14	NONE (DIRECT-MOUNT)
3"	550 IN-LB	F07	14MM	C-1000(DA&SR)	NONE	(4) M8X 1.25P x 40MM w/Lockwashers	17M14	NONE (DIRECT-MOUNT)
4"	1000 IN-LB	F10	17MM	C-2250(DA&SR)	NONE	(4) M10X 1.5P x 48MM w/Lockwashers	22M17	NONE (DIRECT-MOUNT)
6"	1600 IN-LB	F10 & F12	17MM	C-2250 (DA)	NONE	(4) M10X 1.5P x 50MM w/Lockwashers	22M17	NONE
6"	1600 IN-LB	F10 & F12	17MM	C-3650SR	NONE	(4) M10X 1.5P x 50MM w/Lockwashers	27M17	(DIRECT-MOUNT)

NOTE 1: SR UNITS SHOWN ARE FOR "ON-OFF" SERVICE ONLY- FOR POSITIONING APPLICATIONS, CONTACT FACTORY.